

PROFESSIONAL RANGE

# EYE-1000-FW

1000TVL, 3.6MM LENS, 24PCS IR LEDS,  
15-25M IR DISTANCE.

Armoured  
Housing



Day & Night



IP66



Dual Ring  
Design



Colour/Mono



Auto  
Gain Control



Auto White  
Balance



3-Axis  
Gimble



15-25m  
IR Range



IR Cut  
Filter



## EYE-1000-FW SPECIFICATIONS

CCD	1/3" Digital Sensor 1099
DSP	CMOS
TVL	1000TVL
Lens	3.6mm Fixed Lens
IR Range	15m - 25m
IR leds	24pcs
Minimum Illumination	0 lux (IR on)
Signal to Noise Ratio	more than 48dB
Gamma Correction	0.45
Synchronizing System	Internal
Video Output	1.0Vp-p Composite Video Output, 75 Ohm
Effective Pixels	NTSC: 768x494,PAL:752x582
Auto Electric Shutter	Auto (NTSC: 1/60 ~ 1/100,000sec, PAL: 1/50 ~ 1/100,000sec)
Day & Night	Color / B&W / Auto / Ext
White Balance	Auto
Automatic Gain Control	Built in
IP Rating	IP66
Power Supply	DC12V±10%
Dimensions	93 x 80mm
Weight	350g
Scanning System	2:1 Interlace
Current Consumption	50mA (IR OFF) 120mA ( IR ON )
Storage Temperature	-20° +60°
Operating Temperature	-10° +50°



## GENERAL FEATURES

- IR LED Range 15-25m
- Day and night selection
- Auto white balance
- Armoured housing
- Colour/ Mono
- Discrete size
- Dual ring design
- Internal/External
- Automatic Gain Control
- IP66 IP Rating
- Easy Install
- 3 Axis Gimble
- Screw base (No IR Reflection)

## DIMENSIONS

93 x 80mm

## COLOUR

WHITE

AVAILABLE IN  
WHITE BLACK & GREY

