

P400-E37-V2G40

Professional 650tvl, 40-50m IR Range CCTV Camera



General Features

- **CCD: 1/3" 960H Exview HAD II CCD**
- **DSP: ENHANCED EFFIO-E**
- **Lens: 2.8-12mm Varifocal**
- **Illumination: 0 Lux (IR LED On)**
- **Res: 650TVL**
- **IR LED: 48pcs**
- **IR Range: 40-50m**
- **Voltage: 12V DC**

Specification

Image Sensor	1/3" 960H Exview HAD II CCD
DSP	Enhanced Effio-E
Horizontal Resolution	COLOR: 650TVL / B/W: 700TVL
Lens	2.8-12mm Mega pixel lens
IR Led	48 PCS
IR Range	40-50 M
Current Consumption	105mA (IR OFF) ,425mA (IR ON)
S/N Ratio	≥52dB (AGC OFF)
Menu	OSD Control
Picture Elements	PAL: 1024 (H) × 596 (V) NTSC: 1028 (H) × 508 (V)
Effective Pixel	PAL: 976 (H) × 582 (V) NTSC: 976 (H) × 494 (V)
Auto Gain Control	AUTO (4 STEP)
White Balance	ATW/PUSH/USER1/USER2/ANTI CR/MANUAL/PUSH LOCK
Back Light Compensation	BLC & HSBLC & ATR (Adaptive Tone Reproduction)
Day/Night	Auto/COLOR / B&W / Infrared LED exposure optimization
Privacy Masking	ON / OFF (4 Zone)
Motion Detection	ON / OFF(4 Zone)
Dynamic Noise Reduction	2D-NR
Language	English/Japanese/Chinese/German /French/Russian/Portuguese/Spanish
Dimensions	240*105*200mm
Weight	1210g
Scanning System	2:1 Interlace
Min Illumination	0 Lux (IR ON)
Auto Electronic Shutter	PAL:1/50-1/100,000S , NTSC:1/60-1/100,000S
Video output	1Vp-p,75Ω
Gamma Correction	0
Power Supply	DC12V±20%
IP Rating	IP66
Storage Temperature	-20°C +60°C
Operating Temperature	-10°C +50°C