

ZONE V-5 Xtra



Now Available:

4 Channel 1TB H.264 DVR

8 Channel 2TB H.264 DVR

16 Channel 2TB H.264 DVR



view online using your smartphone

Packed with advanced features

Korean Manufactured

Access all menus remotely

User friendly software

3 year Dublin based warranty

Storage calculator included

Run VGA and Composite monitors simultaneously


iPhone, Android, Windows mobile remote view

Accidental footage overwrite protection

Easy Network connection

Automatic DDNS, no need for a static IP address

OZONE V-5 Xtra



Smart Viewer Lite and Smart Viewer* Apps allow you to remotely view CCTV using your mobile phone!

*Available from the iTunes App Store and Android Marketplace.
Smart Viewer Lite - free.
Smart Viewer - €0.79

SPECIFICATION

MODEL	HEVR-0412 PLUS	HEVR-0824	HEVR-1648
Triplex Function	Simultaneous Record/Playback/Network		
Video Compression	H.264 Codec (DSP Based)		
Live Display Speed	120/100 FPS	240/200 FPS	480/400 FPS
Recording Speed	120/100 FPS @ CIF 650/50 FPS @ 2CIF 30/25FPS @ D1	240/200 FPS @ CIF 120/100 FPS @ 2CIF 60/50 FPS @ D1	480/400 FPS @ CIF 240/200 FPS @ 2CIF 120/100 FPS @ D1
Average Bit Rate	5.68Kbps~538Kbps (For 1 Camera)		
Video Input	4CH(BNC)	8CH(BNC)	16CH(BNC)
Video Output	1 VGA (1280X1024)/Sub1 Composite (BNC)		
Spot-Out	1 Composite (BNC)		
Screen Division / Live Playback	1,4,6,8,9,16 / 1, 4, 9, 16		
Audio In/Out	1 in (RCA) / 1 Out (RCA)	4 in (RCA) / 1 Out (RCA)	
Alarm In/Out	4 In/ 1 Out (Relay)		
Storage	1 HDD		
Archive	USB Device (HDD, DVD, Thumb Drive) & Network		
USB Port	1 Front + 1 Rear		
PTZ & Keyboard Control	RS-485		
System Control	USB Mouse, Front Button, Remote controller & Keyboard controller		
Network	LAN, DHCP, Dynamic IP, DDNS		
Power	12V Adaptor, 5A, 50~60Hz		
Operating Temperature	0 ~ 40 degrees celcius / 10 ~ 90% NC		
Dimension (mm)/Weight (kg)	318 x 250 x 58 (H), 1.3U CASE / 1.5kg		
RemoteSW	CMS, Web Browser, PDA, Smart Phone		

MAIN FEATURES

Live Display	OSD Border Colour	On/Off Selectable
Search	Calendar/ Event Search	Search by time/ Search by Event
Playback	Playback Speed Audio Play	Variable Playback (Max .64x) Synchronized with Video
System	Video Covert PTZ Motion Area Setting Time Synchronization User Authority System Reliability Firmware Upgrade	Video will be hidden Live & Playback mode but it will be recorded Supported most of PTZ protocol, Preset up to 255 Adjustable GRID (12x12), 10 Steps Sensitivity Level Auto Time Sync, by NTP server Each user group has different function Watch-Dog, Auto-Recovery after power failure Via USB Device
	Configuration Export & Import S.M.A.R.T Alarm	Setting configuration copy and paste to other DVR via USB Auto-Detect & monitoring the HDDs problem
Record	Resolution Setting Recording Quality Control Recording Schedule Pre/post recording	By each camera for different resolution setting (CIF/2CIF/D1) 5 levels (low/standard/high/highest/super) By hour, by day, by recording mode, by alarm, by channel Max. 5 seconds / Max. 180 seconds
Archive	Archive Device/Format Player	CD/ DVD/ USB device/ AVI file Backup player / Windows Media Player etc
Network	Network Support Type Bandwidth Limit Net Client & Web Server Port E-mail notification System Configuration Two-way audio	LAN / DHCP / DDNS 56KB~8192KB (MAX) or User Selectable Programmable by User E-mails to specific users to notify events Full setup configuration over network Communication with RemoteSW
Others	Watermark	Watermarked Video & Audio for security