

COG-6MP-FISHEYE-FW

6MP PANORAMIC IR NETWORK FISHEYE



- 1/1.8" 6Megapixel progressive scan STARVIS™ CMOS
- H.265/H.264 triple-stream encoding
- Max 25/30fps@6M(3072x2048)
- Multiple dewarped Mode
- Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Smart detection
- Intelligent Function
- Max. IR LEDs length 10m
- Micro SD memory, IP67, IK10, PoE



System Overview

This fisheye camera is an expert at panoramic surveillance with low-profile design. With a fisheye lens, the camera can provide a high quality 180° or 360° panoramic views without blind spots, making it ideal for wide and open areas, such as airports, shopping malls, banks, hotels, stores, offices and more. The camera can offer different views including 360° overview and dewarped views such as panorama view, double views and quad views.

Functions

True Day/Night

A day/night mechanical IR cut filter makes this camera ideal for applications with fluctuating lighting conditions, delivering colour images during the day and automatically switching to monochrome as the scene darkens.

Panoramic

Panoramic cameras provide 180°, 360° full range of video scene, bringing people a new sense of real live and interactive experience. There are two kinds of panoramic camera, single lens fisheye camera and multi-lens camera, both of them can offer 180-degree & 360-degree panoramic image. Through working together with PTZ camera which offer whole scene and region details at same time. It provided new surveillance experience to end user and improved the surveillance quality.

Business intelligent analysis (Heatmap)

This fisheye camera also supports advanced intelligent feature like heat map besides basic IVS functions. The heatmap function can be applied to business intelligence and bring extra values to customers. The heat map function based on a moving object in time of space movement for analysis, find the most active area and output the report, which is to provide valuable data support for commercial applications.

Smart IR

With IR illumination, detailed images can be captured in low light or

total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 10m (33ft).

HEVC(H.265)

H.265 ITU-T VCEG is a new video coding standard. H.265 Following standard developed around the existing video coding standard H.264, some retain the original technology, while some of the relevant technology to improve the new technology uses advanced technology to improve the relationship between the code stream, encoding quality, and the delay between algorithm complexity, optimize settings specific contents include: Improve compression efficiency, improve the robustness and error recovery capabilities, real-time to reduce the delay, reduce channel acquisition time and a random access delay, reduce complexity, etc

Protection (IP67, IK10, wide voltage)

Supporting ±25% input voltage tolerance, this camera suits even the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. IP67 is supported by the camera, which makes it suitable for both indoor and outdoor environments. IK10 compliance enables the camera to sustain the equivalent of 55 kg (120lbs) force.

Technical Specification				
Camera				
Image Sensor	1/1.8" 6Megapixel progressive scan CMOS			
Effective Pixels	3072(H)x2048(V)			
RAM/ROM	1024MB/128MB			
Scanning System	Progressive			
Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s			
Minimum Illumination	0.002Lux/F2.0(Colour,1/3s,30IRE) 0.02Lux/F2.0(Colour,1/30s,30IRE) 0Lux/F2.0(IR on)			
S/N Ratio	More than 50dB			
IR Distance	Distance up to 10m(33ft)			
IR On/Off Control	Auto/ Manual			
IR LEDs	3			
Lens				
Lens Type	Fixed			
Mount Type	Board-in			
Focal Length	1.7mm			
Max. Aperture	F2.0			
Angle of View	H: 180°, V:180°			
Optical Zoom	N/A			
Focus Control	Fixed			
Close Focus Distance	N/A			
DORI Distance	Detect	Observe	Recognize	Identify
	28m(92ft)	11m(36ft)	6m(19ft)	3m(9ft)
Pan/Tilt/Rotation				
Pan/Tilt/Rotation Range	N/A			
Intelligence				
IVS	Tripwire, Intrusion			
Advanced Intelligent Functions	Heat Map			
Video				
Compression	H.265/H.264			
Streaming Capability	3 Streams			
Resolution	6M(3072x2048)/ 4M(2048x2048)/ 3M(2048x1536)/ UXGA(1600x1200)/ 1.3M(1280x960)/ D1(704x576/704x480)/ CIF(352x288/352x240)			
Frame Rate	Main Stream: 6M(1~25/30fps)			
	Sub Stream: D1(1 ~ 25/30fps)			
	Third Stream: 1.3M(1 ~ 25/30fps)			
Bit Rate Control	CBR/VBR			
Bit Rate	H.265: 3Kbps~ 9984Kbps H.264: 8Kbps~ 16384Kbps			
Day/Night	Auto(ICR) / Colour / B/W			
BLC Mode	BLC / HLC / DWDR			
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual			
Gain Control	Auto/Manual			
Noise Reduction	3D DNR			
Motion Detetion	Off / On (4 Zone, Rectangle)			
Region of Interest	Off / On (4 Zone)			
Electronic Image Stabilization(EIS)	N/A			
Smart IR	Support			
Defog	Support			
Digital Zoom	16x			
Flip	N/A			
Mirror	N/A			
Privacy Masking	Off / On (4 Area, Rectangle)			
Audio				
Compression	G.711a/G.711Mu/AAC/ G.726			
Network				
Ethernet	RJ-45 (100/1000Base-T)			
Protocol	HTTP;HTTPS;TCP;ARP;RTSP;RTP;UDP;SMTP;FTP;DHCP;DNS;DDNS;PPPOE;IPv4/v6;QoS;UPnP;NTP;Bonjour;802.1x;Multicast;ICMP;IGMP;SNMP			
Interoperability	ONVIF, PSIA, CGI			
Streaming Method	Unicast / Multicast			
Max. User Access	10 Users/20 Users			
Edge Storage	NAS Local PC for instant recording Mirco SD card 128GB			
Web Viewer	IE, Chrome, Firefox, Safari			
Management Software	Smart PSS, DSS, Easy4ip			
Smart Phone	IOS, Android			
Certifications				
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B			
Interface				
Video Interface	N/A			
Audio Interface	1/1 channel In/Out, 1 Built-in Mic			
RS485	N/A			
Alarm	2 channel In: 5mA 5VDC 2 channel Out: 1A 30VDC / 0.5A 50VAC			
Electrical				
Power Supply	DC12V, PoE (802.3af)(Class 0)			
Power Consumption	<12W			

Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	Φ149.8mm×50.7mm(Φ5.9"×2")
Net Weight	0.58kg(1.28lb)
Gross Weight	1.0kg(2.2lb)

Dimensions (mm/inch)

