

DS-1006KI Series Keyboard

DS-1006KI PTZ Controller



Features and Functions

- 128 x 64 screen
- 4-axis joystick
- Connectable to the Multi-functional Video Center (MVC) and Matrix Access Gateway (VAG) by RS-422 serial port, and shortcut operation of camera/camera groups switch on video wall
- Connectable to DVR by RS-485 serial port, and operation of front panel buttons
- Connectable to dome by RS-485 serial port and realize PTZ control and picture capture by joystick operation
- 16 user accounts management: 1 admin and 15 operators
- System upgrade and import / export of configuration files by USB-flash disk
- Captured pictures(FAT32) can be stored in U-flash disk



Specifications

Model		DS-1006KI
System	LCD screen	128 x 64 pixel screen
	Joystick	4-axis joystick
	Control mode	RS-232, RS-422, RS-485
External Interfaces	Serial interface	1 RS-232, 1 RS-422, 1 RS-485
	USB interface	1 × USB 2.0
General	Power supply	12 VDC
	Consumption	≤ 4.5 W
	Working temperature	-10 to +55° C (14 to 131° F)
	Working humidity	10% to 90%
	Dimensions (W × D × H)	435 × 193 × 110 mm (17.1 × 7.6 × 4.3 inch)
	Weight	≤ 1 kg (2.2 lb)

Available Models

DS-1006KI

010000160100