



QVIS® | 4MP IP EYEBALL CAMERA

Superior Image quality • Switchable H.264 / H.265



FEATURES:

- Up to 4 mega pixel high resolution
- Wide dynamic Range
- Privacy masking
- Day and night
- Dual video streams
- Plug and Play with all Qvis NVR's
- 4MP@15FPS
- 3D Digital Noise Reduction
- DC12V & PoE
- IR cut filter
- Onvif 2.4
- IP67 weather-proof protection
- Supports both H.264 and H.265
H265 Twice the compression
using half the hard drive storage
- Superior Image quality

RECOMMENDED NVR:

Click here to find out more



SPECIFICATION		EYE-4MP-FG/W
CAMERA		
Image Sensor		1/3" Progressive Scan CMOS Sensor
Min illumination		0.05 Lux (F1.2), 0 Lux (IR on)
Shutter time		Auto, 1/25 ~ 1/10000s
Lens		3.6mm
Lens Mount		M12
Day & Night		IR cut filter with auto switch
Wide Dynamic Range		>80dB
Digital noise Reduction		3D NR
S/N Ratio		≥50db(AGC OFF)
Privacy Masking		Up to 4 areas
COMPRESSION STANDARD		
Video Compression		H.264/H.265 & MJPEG
H.265 code profile		Main Profile
Video bit rate		32KB ~16Mbps, support VBR, CBR
Dual Stream		Dual-stream encoding
VIDEO		
Max Image Resolution		2688 x 1520
Resolution		2592*1520/2048*1520/1080P(1920×1080)/D1(704×576)/VGA(640×480)/QVGA(320×240)
Frame Rate	Main Stream	2592*1520(1~15fps); 2048*1520/1080P(1 ~ 25/30fps)
	Sub Stream	D1/VGA/QVGA(1 ~ 25/30fps)
NETWORK		
Network Storage		Video record, Picture format
Alarm Trigger		Manual, Automatic (motion detection, alarm, schedule, cycle)
Protocols		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
Alarm data transmission		FTP, E-mail, Browser, CMS
System Compatibility		ONVIF 2.4
INTERFACE		
Communication Interface		1 RJ45 10M/100M Ethernet interface
GENERAL		
Operating Conditions		-20°C~+55°C , Less than 90% RH
Power Supply		DC12V / PoE (802.3af)
Power Consumption		<3W
Weather Proof		IP67
IR Range		Up to 30M
Dimensions		Φ105.5mm*75.5mm
Weight		500gms
Max. User Access		8/20 users, IE, Google, Firefox
Smart Phone		iPhone, iPad, Android